



| MAGNETIC HEX INSERT BIT HOLDERS •HARDENED STEEL |         |        |                |            |                | Magna™, Apex®*                                     |
|-------------------------------------------------|---------|--------|----------------|------------|----------------|----------------------------------------------------|
| Part Numbers                                    |         |        | S              | Shank Size | L              | Other Features                                     |
| Kanebridge                                      | Apex®   | Magna™ | Hex Tool Shank |            | Overall Length |                                                    |
| 27-690                                          | M-490   | 27690  | 1/4            | 1/4        | 2-7/8          | C-ring retainer                                    |
| 27-710                                          | M-490-4 | 27710  | 1/4            | 1/4        | 4              | C-ring retainer                                    |
| 27-750                                          | M-490-6 | 27750  | 1/4            | 1/4        | 6              | C-ring retainer                                    |
| 39-972                                          | M-497   | 39972  | 1/4            | 1/4        | 2-7/8          | No C-ring                                          |
| 40-832                                          | -       | 40832  | 1/4            | 1/4        | 2-31/32        | C-ring retainer, turned body, 1-piece construction |
| 40-833                                          | -       | 40833  | 1/4            | 1/4        | 2-31/32        | C-ring retainer, 1-piece construction              |
| 40-941                                          | M-490-2 | 40941  | 1/4            | 1/4        | 2-1/8          | C-ring retainer                                    |
| 40-942                                          | M-495   | 40942  | 1/4            | 1/4        | 2-31/32        | C-ring retainer, turned body                       |

\*Bit holders meet the same dimensions as those published by the manufacturers of the Apex® and Magna™ brands.

|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applications/<br/>Advantages</b> | Bit holders offer versatility in the bit driving process by (1) extending the reach of the bit from the driving tool to the fasteners, and (2) enabling insert bits to be used with power-driven equipment. All of the bit holders listed above are magnetic to better hold the bit in place within the holder, and to hold the screw on the end of the bit. They are available in various configurations-- single-piece and two-piece construction, straight or turned body, with or without a retaining ring. Extra hard bits are used specifically with case hardened screws. |
| <b>Material</b>                     | <b>Shank:</b> 50BV30 steel (similar to SAE 6150)<br><b>Body:</b> #704 or 707 Stainless steel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Hardness</b>                     | Rockwell C 42 - 48                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

®Apex is a registered trademark of Cooper Industries.

™Magna is a division of Vermont American Corporation.

Kanebridge's bit holders are not manufactured by or connected with the producers of Apex® or Magna™ bit holders.