



Round Head Oval Head



HEAD DIMENSIONS



ROUND HEADS FOR WOOD SCREWS

ASME B18.6.1

Nominal Size	A		H		J		T		M		G		N	Phillips Driver Size	
	Head Diameter		Height of Head		Width of Slot		Depth of Slot		Dimensions of Recess						
									Diameter		Depth		Width		
	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Min		
2	.162	.146	.069	.059	.031	.023	.048	.037	.114	.101	.064	.042	.018	1	
4	.211	.193	.086	.075	.039	.031	.058	.044	.130	.117	.083	.063	.019	1	
5	.236	.217	.095	.083	.043	.035	.063	.047	.154	.141	.074	.046	.027	2	
6	.260	.240	.103	.091	.048	.039	.068	.051	.162	.149	.084	.056	.027	2	
7	.285	.264	.111	.099	.048	.039	.072	.055	.170	.157	.092	.066	.028	2	
8	.309	.287	.120	.107	.054	.045	.077	.058	.178	.165	.101	.075	.030	2	
9	.334	.311	.128	.115	.054	.045	.082	.062	.186	.173	.110	.084	.030	2	
10	.359	.334	.137	.123	.060	.050	.087	.065	.195	.182	.119	.093	.031	2	
12	.408	.382	.153	.139	.067	.056	.096	.073	.249	.236	.125	.099	.032	3	
14	.457	.429	.170	.155	.075	.064	.106	.080	.265	.252	.142	.116	.034	3	



OVAL HEADS FOR WOOD SCREWS

ASME B18.6.1

Nominal Size	A		H	O		J		T		M		G		N	Phillips Driver Size
	Head Diameter		Height of Head			Width of Slot	Depth of Slot	Dimensions of Recess							
			Side Height	Total Height				Diameter		Depth		Width			
	Max	Min	Ref	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Min	
4	.225	.195	.067	.104	.084	.039	.031	.059	.049	.136	.123	.094	.077	.019	1
5	.252	.220	.075	.116	.095	.043	.035	.067	.055	.158	.145	.085	.061	.028	2
6	.279	.244	.083	.128	.105	.048	.039	.074	.060	.178	.165	.105	.080	.030	2
8	.332	.292	.100	.152	.126	.054	.045	.088	.072	.205	.192	.131	.106	.033	2
9	.358	.316	.108	.164	.137	.054	.045	.095	.078	.216	.203	.144	.119	.034	2
10	.385	.340	.116	.176	.148	.060	.050	.103	.084	.261	.248	.142	.118	.037	3
12	.438	.389	.132	.200	.169	.067	.056	.117	.096	.283	.270	.165	.140	.040	3